

YOSS-SEMI AUTOMATIC STRETCH WRAPPING

- ✓ Machine height: 2500 mm
- ✓ Max. pallet dimensions: 2200 mm (H), 1200 mm x 1200 mm (W)
- ✓ Max. pallet weight: 1500 kg
- ✓ 4 wrapping programs:
 - 1- Standart wrapping (Up & Down)
 - 2- Crosswise wrapping
 - 3- Wrapping up
 - 4- While wrapping, waiting on the top of the pallet to cover sheet etc. for upper protection.
- ✓ PLC system
- ✓ Touch screen HMI in 6 different languages (Turkish, English, German, French, Spanish, Arabic)
- ✓ Elevator up-down speed adjustment
- ✓ Ability to adjust turntable speed
- ✓ Able to work on manual mode
- ✓ Film roll diameter 250 mm,
- ✓ Film roll inner diameter 76 mm,
- ✓ Film roll width 500 mm,
- ✓ Colour: Ral 7040-5002 (Gray-Blue)
- ✓ Turntable speed adjustable between 7-12 rpm
- ✓ Automatic pallet height detection by photocell
- ✓ Inverter for soft starting and stopping
- ✓ Turntable thickness: 6 mm
- ✓ Turntable diameter: 1650 mm
- ✓ Power requirement: 220V 50Hz 1 ph
- ✓ Installed power: 1,4 kW
- ✓ The whole electronic system is made with LG/ LS quality
- ✓ Loading ramp is included
- ✓ CE certification
- ✓ Made in Turkey



STRETCH WRAPPING OPTIONS:



- **Option 1:** Cutting Unit
(Cutting film after ending wrapping)



- **Option 2:** Top Press
(While wrapping; products that are likely to fall are fixed by pressure from the piston or motor, preventing possible damage)



- **Option 3:** Pre-Stretch
(Pre-stretch with motor:
Using pre-stretch with motor, from 50% up to 300% savings using Super Power stretch film)

* Requested air pressure: 5-6 bar